

# **AVIVA**

**PRODUCT GUIDE 2025** 





### **TABLE OF CONTENTS**

MODEL	PAGE	MODEL	PAGE
VENTILATION		COOKING	
POWER PACK	3	OTR MICROWAVE	9
AVD-306PSB3 AVM-278PS2 AVM-368PS2		AOTRM243SB AOTRM303SB AOTRS304SB	
AVP34108PS2 AVP44108PS2		RANGE	10
AVP222PSB		ACRE24CSB	
AVP243SB		REFRIGERATION	
AVP283SB		BOTTOM MOUNT	11-12
AVA-306RS2 AVA-366RS2 AVB-306RS2 AVG-306CS2	4-5	ARBM115SB ARBM150SE2 ARBM177SE ARBM188SE4 ARBM188WE4	
AVU243RSB		FRENCH DOOR	13
AVU303RSB AVV-309S2		ARBM184FSE3	
AVV-369S2 AVV-369S2		TOP MOUNT	14-15
SLIDE-OUT AVS243SB AVS303SB	5	ARTM116SB ARTM142SB ARTM180SE ARTM180WE	
CHIMNEY	6-7	WINE CELLARS + BEVERAGE CENTRES	
AVH-308CS2 AVH-368CS2		COMBO	16
AVN-308CS3 AVN-368CS3 AVO-308CS3 AVO-368CS3		BSC42DB3 VWD42S2 WINE CELLARS	17-18
AVT243CSB2 AVT303CSB2 AVW-308CS2 AVW-368CS2		CWC46DS2 VPC46DS3 ABWC232SS ABWC1622SS	
ISLAND	8	BEVERAGE CENTRE	19
AVI-366IS4 AVI-369IS3		CBC140SS3	_
		WARRANTY	20





### **POWER PACK**

### **MODEL**

### **FINISH**

### SIZE (W x D)







### AVD-306PSB3

### **BLACK GLASS**

29 ½" x 11 1½6"

- Power: 600 CFM, 5-speeds
- Lighting: 2 LED strips, 1.5W (included)
- Controls: Electronic LED controls
- Auto delay-off timer function
- Aluminum mesh filter w/peripheral plate
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 3.7A

AVM-278PS2 AVM-368PS2

201-GRADE SS

27 <sup>3</sup>/<sub>4</sub>" x 11 <sup>3</sup>/<sub>8</sub>" 35 <sup>1</sup>/<sub>2</sub>" x 11 <sup>3</sup>/<sub>8</sub>"

- Power: 860 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Mechanical push buttons
- 2 sets of filters: Aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" and 8" round top
- Electrical requirements 120V / 60Hz / 2.7A





### AVP-34108PS2 AVP-44108PS2

430-GRADE SS

34 %" x 18" 44" x 18"

- Power: 1000 CFM, 4-speeds
- Lighting: 2 bulbs frosted LED 3500k (included)
- Controls: Electronic push buttons with LCD display
- Auto delay-off timer function
- 2 sets of filters: Aluminum micro hole filters and stainless steel baffle filters
- Duct transition: 8" and 10" round top
- Electrical requirements 120V / 60Hz / 3A





### AVP222PSB

### 201-GRADE SS

22" x 11 ¼"

- Power: 200 CFM, 3-speeds
- Lighting: 2 bulbs, 5W LED (included)
- Controls: Mechanical push buttons
- Single aluminum micro hole filter (included)
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 1.3A

### AVP243SB AVP283SB

430-GRADE SS

23 5/8" x 11 3/8" 27 5/8" x 11 5/8"

- Power: 290 CFM, 3-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Mechanical push buttons
- Single aluminum mesh filter (included)
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 2A





### UNDERCABINET MODEL FINISH SIZE (W x D)



### AVA-306RS2 AVA-366RS2

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 600 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor

- 6" hood height
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top and 3 ¼" x 10" rear and top
- Electrical requirements 120V / 60Hz / 2.7A



### AVB-306RS2

201-GRADE SS

29 ½" x 19 ¾"

- Power: 600 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor

- 6" hood height
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top and 3 1/4" x 10" rear and top
- Electrical requirements 120V / 60Hz / 2.7A



### AVG-306CS2

201-GRADE SS

29 ½" x 22"

- Power: 600 CFM, 3-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor

- 6" hood height
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" round top and 3 ¼" x 10" rear and top (included)
- Electrical requirements 120V / 60Hz / 0.5A





UNDERCABINET	MODEL	FINISH	SIZE (W x D)
--------------	-------	--------	--------------



### AVU243RSB AVU303RSB

201-GRADE SS

23 <sup>3</sup>/<sub>4</sub>" x 18 <sup>7</sup>/<sub>8</sub>" 29 <sup>3</sup>/<sub>4</sub>" x 18 <sup>7</sup>/<sub>8</sub>"

- Power: 280 CFM, 2-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Mechanical push buttons
- 5" hood height
- · Aluminum mesh filters
- Duct transition: 3 ¼" x 10" rear and top
- Electrical requirements 110V / 60Hz / 0.45A



### AVV-309S2 AVV-369S2

201-GRADE SS

29 ½" x 22" 35 ½6" x 22"

- Power: 900 CFM, 4-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Dual motor
- $\bullet$  9  $^{13}\!\!/_{16}$ " hood height
- Stainless steel baffle filters (included)
- Duct transition: 8" round top
- Electrical requirements 120V / 60Hz / 2.7A

**SLIDE-OUT** 

### **MODEL**

**FINISH** 

SIZE (W x D)



### AVS243SB AVS303SB

SS FRONT TRIM

23 %" x 11" 29 ½" x 11"

- Power: 290 CFM, 3-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Mechanical slider
- Depth when open: 17 3/4"
- Overall height: 10 3/4"
- White body with stainless front trim
- · Aluminum mesh filter
- Duct transition: 6" round top
- Electrical requirements 120V / 60Hz / 2A





CHIMNEY	MODEL	FINISH	SIZE (W x D)
---------	-------	--------	--------------



### AVH-308CS2 AVH-368CS2

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- 2 sets of filters: aluminum micro hole & stainless steel baffle (included)
- Duct transition: 6" and 8" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-884S-22 (884mm high)
- Electrical requirements 120V / 60Hz / 2.7A



### AVN-308CS3 AVN-368CS3

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD Display
- Auto delay-off timer function
- Clean filter reminder
- 2 stainless steel baffle filters (included)
- Duct transition: 6" & 8" round top
- and 3" ¼ x 10" rear and top
   Chimney (ducted out) for
- ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-884S-22 (884mm high)
- Electrical requirements 120V / 60Hz / 2.7A



### AVO-308CS3 AVO-368CS3

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speedsLighting: 2 bulbs, 3W LED
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- 2 stainless steel baffle filters (inlcuded)
- Duct transition: 6" & 8" round top and 3" 1/4 x 10" rear and top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-780S-22 (780mm high)
- Electrical requirements 120V / 60Hz / 2.7A





CHIMNEY MODEL FINISH SIZE (W x D)



AVT243CSB2 AVT303CSB2

430-GRADE SS

29 ½" x 19 ½"

23 %" x 19 11/16"

- Power: 290 CFM, 3-speeds
- Lighting: 2 bulbs, 2W LED (included)
- Controls: Mechanical push buttons
- 2 aluminum micro-hole filters
- Duct transition: 6" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Electrical requirements 110V / 60Hz / 1.15A



AVW-308CS2 AVW-368CS2

201-GRADE SS

29 ½" x 19 ¾" 35 ½" x 19 ¾"

- Power: 860 CFM, 6-speeds • Lighting: 2 bulbs, 3W LED
- Lighting: 2 bulbs, 3W LED (included)
- Controls: Soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- 2 sets of filters: aluminum micro hole & stainless steel baffle (inlcuded)
- Duct transition: 6" and 8" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-800S2 (800mm high)
- Electrical requirements 120V / 60Hz / 2.7A





ISLAND MODEL FINISH SIZE (W x D)



### AVI-366IS4

430-grade SS + Black glass frame

35 ¼" x 23 5/8"

- Power: 600 CFM, 4-speeds
- Lighting: 4 square LED lights, 2W (included)
- Control: Electronic LED controls display at front and rear of hood
- Auto delay-off timer function
- 3 Aluminum micro hole filters with stainless steel peripheral plate
- Duct transition:6" round top
- Chimney (ducted out) for ceiling heights up to 9'0'
- Electrical requirements 120V / 60Hz / 2.7A



### **AVI-369IS3**

201-GRADE SS

35 ½" x 23 %"

- Power: 900 CFM, 6-speeds
- Lighting: 4 bulbs, 2W LED (included)
- Controls: Electronic soft touch with LCD display
- Auto delay-off timer function
- Clean filter reminder
- Aluminum micro-hole filters (included)
- Duct transition: 6" and 8" round top
- Chimney (ducted out) for ceiling heights up to 9'0"
- Optional accessory: Chimney extension AD-860S2 (860mm high)
- Electrical requirements 120V / 60Hz / 2.7A

### **VENTILATION - MODEL NUMBER NOMENCLATURE**

Α	AVIVA
V	Ventilation
LETTER	Model name
##	Size
#	CFM (1st digit)
C/I/P	Type of Hood: Chimney, Island, Power Pack
B/S	Color: Black / Stainless Steel
#	Generation

VENTILATION WARRANTY: 1-year parts and labor

<sup>\*</sup>Both AVI-366IS4 and AVI-369IS3 Island Hoods can be operated from the front and back side of the hood.





### COOKING

### **OTR MICROWAVE**

### MODEL

### **FINISH**

### SIZE (W x D)



AOTRM243SB

Black glass + SS trims

23 %" x 16 3/4"

- Capacity: 1.4 cu. ft.
- Power: 1000 Watts, 10 levels.
- Ventilation: 300 CFM, 2-speed
   Recessed handle, left-swing
- Duct transition: 3" ¼ x 10" top and rear
- 2 aluminum mesh filters (included)
- Convertible to ductless venting Electrical requirements: with charcoal filters (included)
- Controls: Soft touch electronic with LED display
- Multiple cooking modes, including Sensor Cooking
- Overall Height: 17 1/2"
- Lighting: 2 interior lights
  - 120V / 20A / 60Hz-2450Mhz



### AOTRM303SB

Black glass + SS front

29 %" x 17 %"

- Capacity: 1.7 cu. ft.
- Power: 1000 Watts, 10 levels.
- Ventilation: 300 CFM, 2-speed
- Duct transition: 3" 1/4 x 10" top and rear
- 2 aluminum mesh filters (included)
- Convertible to ductless venting Lighting: 2 interior lights with charcoal filters (included) • Electrical requirements:
- Controls: Soft touch electronic with LED display
- · Heavy duty aluminum handle, left-swing
- · Multiple cooking modes, including Sensor Cooking
- Overall Height: 16 1/8"

  - 120V / 20A / 60Hz-2450Mhz



### AOTRS304SB

Black glass + SS trims

29 1/8" x 18 13/16"

- Capacity: 1.2 cu. ft.
- Power: 1000 Watts, 10 levels.
- Duct transition: 9 13/16" x 2 5/8" top and rear
- 1 aluminum mesh filter (included)
- Convertible to ductless venting Electrical requirements: with charcoal filter (included)
- Controls: Soft touch electronic with LED display
- Ventilation: 400 CFM, 4-speed Recessed handle, left-swing
  - Multiple cooking modes, including Sensor Cooking
  - Overall Height: 11 3/8"
  - Lighting: 2 interior lights

  - 120V / 20A / 60Hz-2450Mhz



### **COOKING**

RANGE MODEL FINISH SIZE (W x D)



ACRE24CSB Black glas

Black glass + SS trims

23 ½" x 23 ½"

**AVIVA** 

- Ceran-top electric range
- 4 electric zones:
   Right-Front: 6", 1200W
   Right-Rear: 8", 2000W
   Left-Front: 8", 2000W
   Left-Rear: 6", 1200W
- Cooking surface indicator lights:
   On/Off each element Hot-surface
- Oven indicator light
- Oven light
- Knob controls
- LED display for clock & timer

- True convection oven:
   Bake element: 2300W
   Broil element: 2600W
   Convection element: 2300W
- Oven capacity: 2.44 cu/ft
- 6 rack levels
- Includes 2 racks
- Bottom storage drawer
- Electrical requirements: 240V / 60Hz / 35-39.6A

# OTR MICROWAVE MODEL NUMBER NOMENCLATURE

Α	AVIVA
OTR	Over-The-Range
M/S	Microwave / Slim
##	Size
#	CFM (1st digit)
S	Color: Stainless
В	Builder-focused

OTR MICROWAVE WARRANTY: 1-year parts and labor

### COOKING RANGE MODEL NUMBER NOMENCLATURE

Α	AVIVA
С	Cooking
R	Range
E	Electric
##	Size
С	Convection
S	Color: Stainless
В	Builder-focused

COOKING RANGE WARRANTY: 2-years parts and labor

23 ½" x 27" x 68"



### REFRIGERATION


### **BOTTOM MOUNT** MODEL **FINISH** SIZE (W x D x H)











- refrigerator-freezer • Capacity: 11.5 cu.ft.
- (Fridge 8.3 + Freezer 3.2)
- Flat door design
- Counter-depth

ARBM115SB

- Recessed, pocket door handle
- Reversible doors
- Internal electronic soft touch controls
- Interior LED lighting
- Frost-free, multi-airflow cooling system
- 3 glass shelves
- 1 large + 2 small door bins
- Large capacity crisper and 1 deli tray
- Freezer includes 2 glass shelves and 1 drawer
- Energy Star® rated
- R600A Refrigerant gas
- Inverter compressor
- Electrical requirements 120V / 60Hz / 15A



### ARBM150SE2

STAINLESS STEEL

STAINLESS STEEL

27 5/8" x 26 1/2" x 67 3/4"

- Freestanding, bottom-mount refrigerator-freezer
- · Capacity: 14.8 cu.ft. (Fridge 10.6 + Freezer 4.2)
- Slightly curved door design
- · Counter-depth
- Recessed door handles
- Reversible doors
- Door open alarm
- Internal electronic soft touch controls
- Soft interior LED Lighting
- Multi airflow, ambient cooling system
- Precise temperature control
- Super Cool and Super freeze function
- 3 adjustable glass shelves
- 3 large + 2 adjustable door bins
- · Large capacity crisper
- Freezer includes manual ice-maker with ice bin, 2 large drawers + 1 small tray
- Energy Star\* rated
- R600A Refrigerant gas
- Inverter compressor
- Electrical requirements 120V / 60Hz / 15A





### REFRIGERATION

### **BOTTOM MOUNT** MODEL **FINISH** SIZE (W x D x H)











- Freestanding, bottom-mount refrigerator-freezer
- Capacity: 17.7 cu. ft. (Fridge 12.7 + Freezer 5)
- Flat-door design
- Metallic liner & backsplash
- Recessed door handles
- · Reversible doors
- Door open alarm
- Internal electronic soft touch controls
- Soft interior LED lighting
- Multi airflow, ambient cooling system
- Precise temperature control
- Super Cool and Super freeze function
- 3 adjustable glass shelves
- 1 large + 4 small height -adjustable door bins
- 2 half-width crispers
- Freezer includes 2 large drawers
- + 2 small travs
- Energy Star® rated
- R600A Refrigerant gas
- Inverter compressor
- Electrical requirements 120V / 60Hz / 15A

### ARBM188SE4 ARBM188WE4

STAINLESS STEEL WHITE

29 ½" x 31 ½" x 66 ¾"

- Freestanding, bottom-mount, single-door slide-out drawer freezer
- Capacity: 18.7 cu. ft. (Fridge 13.1 + Freezer 5.6)
- Flat-door design
- Recessed door handles
- Reversible fridge door
- Door open alarm
- Internal electronic touch controls
- Interior Lighting LED lights
- Dual temperature control system
- 2 height-adjustable glass shelves
- 1 large + 3 small height-adjustable door bins
- 2 crispers with humidity control
- Freezer includes 2 large slide-out bins (1 white + 1 clear)
- Energy Star\* rated
- R600A Refrigerant gas
- Inverter compressor
- Electrical requirements 120V / 60Hz / 15A



ARBM188WE4





### **REFRIGERATION**

### FRENCH DOOR MODEL FINISH SIZE (W x D x H)





 ARBM184FSE3
 STAINLESS STEEL
 29 ½" x 31" x 66 ¾"

- Freestanding, bottom-mount, French-door, slide-out drawer freezer
- Capacity: 18.4 cu. ft. (Fridge 12.8 + Freezer 5.6)
- Flat-door design
- Recessed door handles
- Internal electronic touch controls
- Door open alarm
- Interior Lighting LED lights
- Precise temperature control
- 2 height-adjustable glass shelves
- 6 large door bins (3 on each side)
- 2 crispers with humidity control
- Freezer includes 2 large storage bins (1 white + 1 clear)
- Energy Star\* rated
- R600 Refrigerant gas
- Inverter compressor
- Electrical requirements 120V / 60Hz / 15A





23 ½" x 29" x 59 ½"



### REFRIGERATION

### TOP MOUNT MODEL FINISH SIZE (W x D x H)



### • Freestanding, top mount refrigerator-freezer

STAINLESS STEEL

- Capacity: 11.6 cu. ft. (Fridge 8.4 + Freezer 3.2)
- Flat door design

ARTM116SB

- Recessed door handles
- Reversible doors
- Internal electronic soft touch controls
- Interior LED lighting
- Frost-free, multi-airflow cooling system
- 3 glass shelves
- 2 large + 4 small door bins
- + bottle/pop can holder bins
- 2 crispers
- Freezer includes 1 wire shelf and 2 large door bins
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A



# DMPVIS



### ARTM142SB

STAINLESS STEEL

27 ½" x 29" x 60 ½"

- Freestanding, top mount refrigerator-freezer
- Capacity: 14.2 cu. ft. (Fridge 10.6 + Freezer 3.6)
- Flat door design
- Recessed door handles
- Reversible doors
- Internal electronic soft touch controls
- Interior LED lighting
- Frost-free, multi-airflow cooling system
- 2 adjustable glass shelves
- 2 large door bins
- 1 large crisper
- Freezer includes 1 glass shelf and 2 large door bins
- Energy Star® rated
- R600A Refrigerant gas
- Electrical requirements 120V / 60Hz / 15A





### REFRIGERATION

TOP MOUNT MODEL FINISH SIZE (W x D x H)





STAINLESS STEEL WHITE

29 ¾" x 30 ¾" x 66 ½"

- Freestanding, top mount refrigerator-freezer
- Capacity 18 cu. ft. (Fridge 14 + Freezer 4)
- Flat-door design
- Recessed door handles
- Reversible doors
- Internal electronic touch controls
- Interior LED lighting
- Multi airflow cooling
- Dual temperature control system
- 2 height-adjustable
- + 1 fixed glass shelves in fridge
- 2 large + 2 small fridge door bins
- 2 crispers with humidity control
- Freezer includes 1 height-adjustable glass shelf & 2 large door bins
- Energy Star® rated
- R600A Refrigerant gas
- Inverter compressor
- Electrical requirements 120V / 60Hz / 15A



ARTM180WE

### **REFRIGERATION - MODEL NUMBER NOMENCLATURE**

Α	AVIVA
R	Refrigerator
BM/TM	Bottom-mount / Top-mount
##	Capacity
F	French Door
S/W	Stainless Steel / White
E	Energy Star
#	Generation

WARRANTY: 2-years labor and replacement parts. Additional 3-year warranty, for a total of 5 years on the sealed system (components only).



23 ¾" x 23 ¼" x 34 ½"



### **WINE CELLARS & BEVERAGE CENTRES**

COMBO MODEL FINISH SIZE (W x D\* x H)

BSC42DB3



• Dual-zone, temperature range

- per zone: 39°- 64°F / 4-18°C • Side by side configuration
- Built in or freestanding
- Flush fit installation
- Capacity: 21 bottles + 64 cans
- Door open alarm
- Door open alarm
- High-temperature alarm
- Soft-touch electronic controls
- Made of vitrified black glass
- + tinted and UV treated glass with Low-E argon gas
- SS Tubular Pro handle
- Interior lighting White LED
- Stainless steel kick plate
- 6 full-extension, ball-bearing metal racks with black wooden frontage
- + 3 glass shelves
- R600a Refrigerant gas



VWD42S2

SS + GLASS

BLACK + GLASS

23 1/8" x 23 3/4" x 34 1/2"

- Dual-zone temp. range per zone: 39° - 64°F / 4 - 18°C
- Side by side configuration
- Each side convertible to wine or beverage cooler
- Built in or freestanding
- Flush fit installation
- Total Capacity: 42 bottles or 21 bottles + 64 cans
- Door open alarm
- High-temperature alarm
- Soft-touch electronic controls

- Seamless, stainless steel doors
- Tinted glass with Low-E Argon gas
- SS tubular pro handle
- LED lighting color options: White, Blue, Yellow
- Stainless steel kick plate
- 12 wooden shelves with stainless steel front trim
- Includes 3 glass shelves for beverage configuration
- Sabbath mode
- R600a Refrigerant gas

<sup>\*</sup>Depth does not include handle.





### WINE CELLARS & BEVERAGE CENTRES

### **WINE CELLAR**

MODEL

**FINISH** 

SIZE (W  $\times$  D\*  $\times$  H)

CWC46DS2

SS + GLASS

23 ½" x 23 ¾" x 34"

- Dual-zone, temperature range per zone: 41° - 64°F / 5 - 18° C
- Built in or freestanding
- Flush fit installation
- Capacity: 46 bottles
- Seamless, stainless steel door - field reversible
- Door open alarm
- High-temperature alarm
- Electronic touch controls

- UV tinted glass with Low-E Argon gas
- SS Tubular Pro handle
- Interior lighting White LED
- · Black kick plate
- 5 soft-closing, full-extension, ball-bearing metal racks with wood front trim
- R600a Refrigerant gas



VPC46DS3

SS + GLASS

23 ¾" x 23 ½" x 34 ½"

- Dual-zone temperature range per zone: 39° - 64°F / 4 - 18°C
- Built in or freestanding
- Flush fit installation
- Capacity: 46 bottles
- Seamless, stainless steel door - field reversible
- Door open alarm
- High-temperature alarm

- Soft-touch electronic controls
- Tinted glass with Low-E Argon gas
- SS Tubular Pro handle
- Interior lighting White LED
- Stainless steel kick plate
- 5 full-extension, ball-bearing wooden shelves with stainless steel front trim
- R600a Refrigerant gas



\*Depth does not include handle.

ABWC232SS

SS + GLASS

15" x 22 %16" x 34 1/4"

- Dual-zone temperature range: Upper zone: 41° - 54°F / 5 - 12°C • UV treated glass door Lower zone:  $54^{\circ}$  -  $65^{\circ}$ F / 12 -  $18^{\circ}$ C • SS Tubular Pro handle
- Built in or freestanding
- Flush fit installation
- Capacity: 23 bottles
- Seamless, stainless steel door
- field reversible
- Door open alarm
- High-temperature alarm

- · Soft-touch electronic controls

- · Blue LED lighting
- · Stainless steel kick plate
- 5 full-extension wooden shelves with stainless steel front trim
- · Sabbath mode
- R600a Refrigerant gas





### **WINE CELLARS & BEVERAGE CENTRES**

**WINE CELLAR - FULL SIZE** 

MODEL

**FINISH** 

SIZE (W  $\times$  D\*  $\times$  H)

ABWC1622SS

SS + GLASS

23 ½" x 26 %16" x 69 5/16"

- Dual-zone temperature range:
- Lower zone: 54° 65°F / 12 18°C SS Tubular Pro handle
- Built in or freestanding
- Flush fit installation
- Capacity: 162 bottles
- - field reversible
- Door open alarm • High-temperature alarm

- Soft-touch electronic controls
- Upper zone: 41° 54°F / 5 12°C UV treated glass door

  - Blue LED light strips
  - Stainless steel kick plate
- Capacity: 162 bottles
   Seamless, stainless steel door
   13 full-extension wooden shelves with stainless steel front trim
  - Sabbath mode
  - R600a Refrigerant gas

<sup>\*</sup>Depth does not include handle.





### **WINE CELLARS & BEVERAGE CENTRES**

**BEVERAGE CENTER** 

**MODEL** 

**FINISH** 

SIZE (W  $\times$  D\*  $\times$  H)

CBC140SS3

SS + GLASS

23 ½" x 23 ½" x 34"

- Single-zone, temperature range: 34° 50°F / 1 10°C
  - Built in or freestanding
  - Flush fit installation
  - Capacity: 140 cans
  - Seamless, stainless steel door
  - field reversible
- Door open alarm
- High-temperature alarm

- Electronic touch controls
- UV tinted glass with Low-E Argon gas
- SS Tubular Pro handle
- Interior lighting White LED
- · Black kick plate
- 3 height-adjustable glass shelves
- R600a Refrigerant gas

### WINE CELLARS & BEVERAGE CENTRES - MODEL NUMBER NOMENCLATURE

VP/BS/C	(Series) Vinopazzo / Black (Noire) / C Series
C/B/WC	Cellar / Beverage / Wine Cellar
NUMBER	Capacity
S/D	Single or Dual Zone
S/B	Stainless Steel or Black
#	Generation

WARRANTY: 2-year parts and labor, 5 years on sealed system (parts only).

\*Depth does not include handle.



### WARRANTY

### **VENTILATION AND OTR MICROWAVE**

We warrant our hoods and OTR's against defects in materials and workmanship under ordinary residential use for one (1) full year from the date of original retail purchase. This limited warranty applies to any repair and /or replacement parts. This limited warranty is not subject to improper installation, accident, misuse, neglect, fire or other external causes, alterations, repair or commercial use.

### **COOKING RANGE**

We warrant our cooking ranges against defects in materials and workmanship under ordinary residential use for two (2) full years from the date of original retailpurchase. This limited warranty applies to any repair and /or replacement parts. This limited warranty is not subject to improper installation, accident, misuse, neglect, fire or other external causes, alterations, repair or commercial use.

### REFRIGERATION AND WINE & BEVERAGE CENTRES

Aviva refrigerators, wine cellars and beverage centres carry a two (2) year limited warranty on both parts and labor. Aviva warrants for two (2) years, to the purchaser of every new unit, the cabinet and all parts thereof, to be free from defects in material or workmanship, under normal and proper use and maintenance service as specified by Aviva and upon proper installation and start-up in accordance with the instruction manual supplied with the Aviva unit. Any parts covered under this warranty that are determined by Aviva to have been defective, within the above said period, are limited to the repair or replacement, including labor charges, of defective parts or assemblies.

In addition to the 2 year warranty period stated above, Aviva warrants its hermetically sealed compressor to be free from defects in both material and workmanship, under normal and proper use and maintenance, for a period of an additional 36 months (a total of 5 years on hermetically sealed compressor). The above said extended compressor warranty applies only to hermetically sealed parts of the compressor and DOES NOT apply to any other parts or components, including, but not limited to, cabinet, paint finish, temperature control, refrigerant, metering device, motor starting equipment, fan assembly, or any other electrical component, etc.

**NOTES** 





110120





NOTES	





NOTES



## **PRODUCT GUIDE 2025 AVIVA**

T 800 361 0799 F 450 682 7943

www.distinctive-online.com info@distinctive-online.com

### **HEAD OFFICE & WAREHOUSE**

2025 Cunard Street Laval QC H7S 2N1

### **WESTERN CANADA WAREHOUSE**

NFI 1020 Derwent Way Delta, BC V3M 5R1

### SERVICE DEPARTMENT

service@distinctive-online.com 800 561 7265

### ORDER DESK

orderdesk@distinctive-online.com